



Stal ciągniona

oznaczenie stali			zakres wymiarowy w mm			
Werkstoff	gat.	DIN 	671 tol. h9	178	174	176
			Ø	■	□	⬡
1.0037	St3s	St37k (S235JRC)	3 - 160	4 - 120	6x3 - 500x50	7 - 100
1.0401	15	C15k (C15E)	6 - 70			
1.0501	35	C35k (C35E)	5 - 160			10 - 65
1.0503	45	C45k (C45E)	4 - 160	10 - 100	15x8 - 200x30	8 - 80
1.0504	45+Pb	C45Pb	10 - 50			
1.0553	18G2A	St52-3k (S355JO)	6 - 120	30 - 100	20x10-100x40	
1.0715	A10X	11SMn30k(9SMn28k)	3 - 160	6 - 100		5 - 100
1.0718	A10X+Pb	11SMnPb30k(9SMnPb28k)	4 - 115	5 - 100		6 - 60
1.0726	A35	35S20	14 - 60			19 - 32
1.0727	A45	46S20 (45S20)	6 - 80			
1.7139	16HG	16MnCrS5	5 - 70			17 - 36
1.7227	40HMT	42CrMoS4V	5 - 90			13 - 65
1.3505	ŁH15	100Cr6	13 - 60			

Inne wymiary i gatunki na zapytanie.

Pręty okrągłe szlifowane

oznaczenie stali			zakres wymiarowy w mm			
Werkstoff	gat.	DIN 	tol. h6			
			Ø	■	□	⬡
1.0501	35	C35k (C35E)	8 - 100			
1.0503	45	C45k (C45E)	10 - 80			
1.0553	18G2A	St52-3k (S355JO)	na zapytanie			